International

Webex Meeting Link

May 5, 2022
2:00 PM EST to 5 PM EST (3 hours)

2. Meeting Conduct.
    a. Identification of Representation/Conflict of Interest
    b. ICC Council Policy 7 Committees: Section 5.1.10 Representation of Interests

    c. ICC Code of Ethics: ICC advocates commitment to a standard of professional behavior that exemplifies the highest ideals and principles of ethical conduct which include integrity, honesty, and fairness. As part of this commitment it is expected that participants shall act with courtesy, competence and respect for others.

3. Roll Call.

4. Approve Agenda

5. Approval of Minutes

6. Administrative issues-staff

7. Subcommittee Reports

8. Action Items
    a. Code Change Proposals
        REPI-97-21 (Ventilation Sampling for Multifam)(HVACR disapprove 6-5-1)
        REPI-126-21(ERI Alternative)

Copyright © 2021 International Code Council, Inc.

MODIFICATION REVIEWED BY THE SUBCOMMITTEE

REPI-97-21 MOD1

IECC®: R403.6.3, R403.6.4 (New)

Proponents:

Aaron Gary, representing Self (aaron.gary@texenergy.org)

2021 International Energy Conservation Code

R403.6.3 Testing.

Each ~~M~~mechanical ventilation system~~s~~ shall be tested and verified to provide the minimum ventilation flow rates required by Section R403.6. Testing shall be performed according to the ventilation equipment manufacturer's instructions, or by using a flow hood or box, flow grid, or other airflow measuring device at the mechanical ventilation fan's inlet terminals or grilles, outlet terminals or grilles, or in the connected ventilation ducts. Where required by the code official, testing shall be conducted by an approved third party. A written report of the results of the test shall be signed by the party conducting the test and provided to the code official.

Exception~~s~~: The following systems are exempt:

1. Kitchen range hoods that are ducted to the outside with 6-inch (152 mm) or larger duct and not more than one 90-degree (1.57 rad) elbow or equivalent in the duct run.
2. Where tested in accordance with R403.6.4, testing of each mechanical ventilation system is not required.

R403.6.4 Dwelling Unit Sampling ~~for R2 multifamily dwelling units~~.

For buildings with eight or more dwelling units ~~testing units~~ ~~complying with R403.6.3~~, the mechanical ventilation systems in the greater of seven ~~units~~ or 20 percent of the dwelling units ~~testing units~~ in the building shall be tested, including a top floor unit, a ground floor unit, a middle floor unit, and the dwelling unit ~~a unit~~ with the largest ~~testing unit~~ conditioned floor area. ~~For each tested unit~~ Where buildings have fewer than eight dwelling units ~~testing units~~, each dwelling unit ~~testing unit~~ shall be tested. Where the ventilation flow rate of a mechanical ventilation system is less than the ~~that does not meet~~ the minimum permitted ventilation flow rate, corrective actions shall be made to the system and the system retested unit it passes. For each dwelling unit that has less ventilation airflow rate than the minimum permitted airflow rate, an additional three units, including the corrected unit shall be tested~~, including a mixture of testing unit types and locations. Where buildings have fewer than eight testing units, each testing unit shall be tested.~~

Where buildings qualify under the scope of Section R101.2 of the International Residential Code, each mechanical ventilation system in each dwelling unit shall be tested.

Copyright © 2021 International Code Council, Inc.

International Energy Conservation Code
Code Change Proposal Tracking Sheet

Proposal #	REPI-127-21 R406 ERI score harmonize with R405 path
CDP ID #	
Code	IECC RE

Copyright © 2021 International Code Council, Inc.

International Energy Conservation Code
Code Change Proposal Tracking Sheet

Proposal #	RECPI-6-21 Committee EV R-3 Proposal
CDP ID #	
Code	IRC

Copyright © 2021 International Code Council, Inc.

Committee Response		

Copyright © 2021 International Code Council, Inc.

R404.4.4 Circuit Capacity. The capacity of electrical infrastructure serving each EV capable space, EV ready space and EVSE space shall have a rated capacity not less than 8.3 kVA (or 40A at 208/240V) for each EV capable space, EV ready space or EVSE space it serves. Where a circuit is shared or managed it shall be in accordance with NFPA 70.

R404.4.5 EVSE Installation. EVSE shall be installed in accordance with NFPA 70 and shall be listed and labeled in accordance with UL 2202 or UL 2594. ~~EVSE shall be accessible in accordance with International Building Code Section 1107.~~

Copyright © 2021 International Code Council, Inc.

Copyright © 2021

Copyright © 2021

ELECTRIC VEHICLE

Copyright © 2021 International Code Council, Inc.

6. The panelboard or other electrical distribution equipment directory shall designate the branch circuit as “For electric vehicle supply equipment (EVSE)” and the outlet or enclosure shall be marked “For electric vehicle supply equipment (EVSE).”

R404.4.4 Circuit Capacity. The capacity of electrical infrastructure serving each EV capable space, EV ready space and EVSE space shall comply with one of the following:

1. A branch circuit shall have a rated capacity not less than 8.3 kVA (or 40A at 208/240V) for each EV capable space, EV ready space or EVSE space it serves. Where a circuit is shared or managed

Copyright © 2021 International Code Council, Inc.

International Energy Conservation Code
Code Change Proposal Tracking Sheet

r[C)1.7 (ode)]TJETQ7.48 580.56 145.021 14085ii52 354.181 14.188 reW nBT/TT1 1 T-

Proposal #	RECPI-4-21
CDP ID #	
Code	IECC RE

Copyright © 2021 International Code Council, Inc.

Vote	Affirmative_____ Negative_____ Table_____ To Subcommittee_____
Date	

Copyright © 2021 International Code Council, Inc.

< (+ ; #
)

2
2